

Tonmind 15W IP Ceiling Speaker with MIC SIP-S01M

1. Two-way intercom communication.
2. PoE eliminates need for local power supply.
3. 48K OPUS Audio Codec enables excellent sound quality.
4. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
5. Compatible with IP Camera VMS via ONVIF.
6. Support Pre-recorded messages.
7. Support HPPT API for alarm in transmit.



Specification:

Audio

Decoding OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

Speaker

Max SPL 96dB

Frequency Response 100Hz ~ 18KHz

Frequency Range 500-2KHZ +-10dB
400-12KHZ +-20dB

Harmonic Distortion 0.1@1kHz

Signal to Noise Ratio 91dB

Network

Security Password protection, IP address filtering, Digest authentication, User access log, firewall

Network Protocol SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP

Network Interface 10/100 Base-TX, RJ45

Support SIP protocol for intergration with VoIP systimes, intergrated with SIP/PBX.

VoIP Support SIP features: secondary/backend SIP server, IPv4 (IPv6 futhur).

Support codecs: OPUS, G711U, G711A, GSM, MP3, WAV.

Amplifier

Amplifier Description Built-in 15W Amplifier

MIC

Built-in MIC Yes

General

Material Metal

Rate Power 15W

Power Supply PoE or DC 12V

Installation In Ceiling

Dimensions 200 x 90 mm

Net Weight 1 KG

Languages English

Warranty 2 years

Package Includes Network Ceiling Speaker
User Manual